Data Sheet

60kW HYDRO-LIFT Single Submersible Pump

Motor Specification	
Motor Rating	60W
Shaft Speed	3510rpm
Electrical Supply	3 Phase / 440V / 60Hz / 150A MRB Required
Enclosure	IP68
Construction	Stainless Steel
Running Current	102A
Starting Current	255A to 408A (Dependent on Generator)
Cables	4C50mm² Power + 4C2.5mm² Control
Pump Specification	
Nominal Flow	507USGPM @ 156PSI (115m³/h @ 10.8BAR)
Max Flow/ Max Head	705USGM (160m³/h) 258PSI (17.8BAR)
Connection Size and Type	5” ASA 150 RF Flange
Weights & Dims (c/w Deployment Caisson)	
Height x Length x Width	273mm x 3361mm x 412mm
Gross Weight	590kg

Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer’s use and for ensuring that Customer’s workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. Further, nothing contained herein shall be taken as a recommendation to manufacture or use any of the herein described materials or processes in violation of existing or future patents. © 2025 OPTIMA Solutions UK Ltd. All Rights Reserved.